

TYPE 125 EIP IWRC: MECHANICAL SPLICED TWO-LEG SPREADERS

	Rope Dia. (")	Rated Capacity (Tons)			Master Link Dia. (")	Alloy Hook WLL Tons
		Degrees				
		60°	45°	30°		
6x19 or 6x36 EIP	1/4	1.1	.91	.65	1/2	1
	5/16	1.7	1.4	1	1/2	1
	3/8	2.5	2	1.4	1/2	1-1/2
	7/16	3.4	2.7	1.9	3/4	2
	1/2	4.4	3.6	2.5	5/8	3
	9/16	5.5	4.5	3.2	7/8	5
	5/8	6.8	5.5	3.9	1	5
	3/4	9.7	7.9	5.6	1	7
	7/8	13	11	7.6	1-1/4	11
	1	17	14	9.8	1-1/2	11
6x36 EIP	1-1/8	21	17	12	1-1/2	15
	1-1/4	26	21	15	1-3/4	15
	1-3/8	31	25	18	1-3/4	22
	1-1/2	37	30	21	2	22
	1-3/4	49	40	28	2-1/4	30
	2	63	52	37	2-1/2	37

Rated Capacities based on design factor of 5.
Horizontal sling angles of less than 30° shall not be used.



Master Link w/
Sub-Assemblies Optional

