

TYPE 215 EIP IWRC: MECHANICAL SPLICE GROMMET



	Sling Body Dia. ("")	Rated Capacity (Tons)					
					Basket Hitch		
					Degrees		
					60°	45°	30°
6X19 OR 6X36 EIP	1/4	1.1	.74	2.1	1.8	1.5	1.1
	5/16	1.6	1.2	3.3	2.8	2.3	1.6
	3/8	2.4	1.6	4.7	4.1	3.3	2.4
	7/16	3.2	2.2	6.4	5.5	4.5	3.2
	1/2	4.1	2.9	8.3	7.2	5.9	4.1
	9/16	5.2	3.7	10	9.1	7.4	5.2
	5/8	6.4	4.5	13	11	9.1	6.4
	3/4	9.2	6.4	18	16	13	9.2
	7/8	12	8.7	25	22	18	12
	1	16	11	32	28	23	16
6X36 EIP	1-1/8	20	14	41	35	29	20
	1-1/4	25	17	50	43	35	25
	1-3/8	30	21	60	52	42	30
	1-1/2	36	25	71	62	50	36
	1-3/4	48	33	95	83	68	48
	2	62	43	124	107	87	62
	2-1/4	77	54	154	133	109	77
	2-1/2	94	66	188	163	133	94
	2-3/4	113	79	225	195	159	113
	3	133	93	265	230	188	133
	3-1/2	176	123	352	304	248	176
	4	225	157	450	389	317	225
	4-1/2	278	194	555	481	392	278

Rated Capacities based on design factor of 5.

Horizontal sling angles less than 30° shall not be used.

Rated Capacities based on D/d ratio of 5.