

TYPE 8P1 7X19: GALVANIZED BRAIDED SLING



7x19

Rope Dia. (")	Sling Dia. (")	Vert	Choker Hitch	Rated Capacity (Tons)			Eye Dimensions (")		Slip Thru Thimble	Heavy Thimble	
				Basket Hitch	Degrees			A			B
					60°	45°	30°				
1/8	9/16	1.1	1	2.2	1.9	1.6	1.1	3	6	ST 10	1/2
3/16	13/16	1.9	1.6	3.7	3.2	2.6	1.9	4	8	ST 16	5/8
1/4	1-1/8	3.3	2.9	6.6	5.7	4.7	3.3	5	10	ST 20	7/8
5/16	1-3/8	5.1	4.5	10	8.9	7.3	5.1	6	12	ST 24	1
3/8	1-11/16	7.3	6.4	15	13	10	7.3	7	14	ST 36	1-1/8

TYPE 8P2 7X19: TWO-LEG GALVANIZED BRAIDED SLING



7x19

Rope Dia. (")	Sling Dia. (")	Single Leg Choker	Rated Capacity (Tons)			Master Link Dia. (")
			Legs in a Choker Hitch			
			Degrees			
			60°	45°	30°	
1/8	9/16	1	1.7	1.4	.98	1/2
3/16	1-3/16	1.6	2.8	2.3	1.6	1/4
1/4	1-1/8	2.9	5	4.1	2.9	1
5/16	1-3/8	4.5	7.8	6.3	4.5	1-1/4
3/8	1-11/16	6.4	11	9.1	6.4	1-1/4

Made with 7x19 GAC component rope.

Rated Capacities in Basket Hitch based on D/d ratio of 25 times the component rope diameter.

Rated Capacities based on pin diameter no larger than natural eye width or less than the nominal sling diameter.

Rated Capacities based on design factor of 5.

Horizontal sling angles less than 30° shall not be used.