

## TYPE 8P3 7X19: THREE-LEG GALVANIZED BRAIDED SLING

7x19	Rope Dia. ("")	Sling Dia. ("")	Single Leg Choker	Rated Capacity (Tons)			Master Link Dia. ("")
				Legs in a Choker Hitch			
				Degrees			
				60°	45°	30°	
1/8	9/16	1	2.5	2.1	1.5	3/4	
3/16	13/16	1.6	4.3	3.5	2.5	3/4	
1/4	1-1/8	2.9	7.5	6.1	4.3	1-1/4	
5/16	1-3/8	4.5	12	9.5	6.7	1-1/2	
3/8	1-11/16	6.4	17	14	9.6	2	



## TYPE 8P4 7X19: FOUR-LEG GALVANIZED BRAIDED SLING

7x19	Rope Dia. ("")	Sling Dia. ("")	Single Leg Choker	Rated Capacity (Tons)			Master Link Dia. ("")
				Legs in a Choker Hitch			
				Degrees			
				60°	45°	30°	
1/8	9/16	1	3.4	2.8	2	1	
3/16	13/16	1.6	5.7	4.6	3.3	1-1/2	
1/4	1-1/8	2.9	10	8.1	5.8	1-3/4	
5/16	1-3/8	4.5	16	13	9	2	
3/8	1-11/16	6.4	22	18	13	2-3/4	



Master Link with  
Sub-Assemblies Optional

Made with 7x19 GAC component rope.  
Rated Capacities based on design factor of 5.  
Horizontal sling angles less than 30° shall not be used.