

# CABLE LAID SLINGS



## TYPE CL15: GALVANIZED CABLE LAID SINGLE PART SLING

	Rope Dia. (")	Vertical	Choker Hitch	Basket Hitch			Eye Dimensions (")		Thimble Dimensions (")		Alloy Hook WLL Tons	
				Degrees			Length	Width	Length	Width		
				60°	45°	30°						
<b>7X7X7</b>	3/8	1.1	.74	2.2	1.9	1.5	1.1	6	3	2.13	1.13	1-1/2
	1/2	1.9	1.3	3.7	3.2	2.6	1.9	8	4	2.75	1.5	2
	5/8	2.8	1.9	5.5	4.8	3.9	2.8	10	5	3.25	1.75	3
<b>7X7X19</b>	3/4	4.1	2.8	8.1	7	5.8	4.1	12	6	3.75	2	5
	7/8	5.4	3.7	11	9.4	7.6	5.4	14	7	4.25	2.25	7
	1	6.9	4.7	14	12	9.7	6.9	16	8	4.5	2.5	7
	1-1/8	8.3	5.8	17	14	12	8.3	18	9	5.13	2.88	11
	1-1/4	9.9	7	20	17	14	9.9	20	10	5.13	2.88	11



## TYPE CL25: GALVANIZED CABLE LAID TWO-LEG SLING

	Rope Dia. (")	Rated Capacity (Tons)			Master Link Diameter (")	Alloy Hook WLL Tons
		60°	45°	30°		
<b>7X7X7</b>	3/8	1.9	1.5	1.1	1/2	1-1/2
	1/2	3.2	2.6	1.9	3/4	2
	5/8	4.8	3.9	2.8	1	3
<b>7X7X19</b>	3/4	7	5.8	4.1	1	5
	7/8	9.4	7.6	5.4	1	7
	1	12	9.7	6.9	1-1/4	7
	1-1/8	14	12	8.3	1-1/4	11
	1-1/4	17	14	9.9	1-1/2	11



Rated Capacities Basket Hitch based on D/d ratio of 10 times the component rope diameter.

Rated Capacities based on pin diameter no larger than natural eye width or less than the nominal sling diameter.

Rated Capacities based on design factor of 5.

Horizontal sling angles less than 30° shall not be used.