

TYPE CL35: GALVANIZED CABLE LAID THREE-LEG SLING

	Rope Dia. (")	Rated Capacity (Tons)			Master Link Diameter (")	Alloy Hook WLL Tons
		60°	45°	30°		
7X7X7	3/8	2.8	2.3	1.6	3/4	1-1/2
	1/2	4.8	3.9	2.8	1	2
	5/8	7.2	5.9	4.2	1	3
7X7X19	3/4	11	8.6	6.1	1-1/4	5
	7/8	14	11	8.1	1-1/2	7
	1	18	15	10	1-3/4	7
	1-1/8	21	18	12	1-3/4	11
	1-1/4	26	21	15	2	11



TYPE CL45: GALVANIZED CABLE LAID FOUR-LEG SLING

	Rope Dia. (")	Rated Capacity (Tons)			Master Link Diameter (")	Alloy Hook WLL Tons
		60°	45°	30°		
7X7X7	3/8	3.8	3.1	2.2	7/8	1-1/2
	1/2	6.4	5.2	3.7	1-1/4	2
	5/8	9.6	7.8	5.5	1-1/4	3
7X7X19	3/4	14	12	8.1	1-1/2	5
	7/8	19	15	11	1-3/4	7
	1	24	19	14	2	7
	1-1/8	29	23	17	2	11
	1-1/4	34	28	20	2-1/4	11



Rated Capacities based on design factor of 5.
Horizontal sling angles less than 30° shall not be used.



Master Link with
Sub-Assemblies Optional