

TYPE SS25 T-304: TWO-LEG STAINLESS STEEL SLING

| | Rope Dia. (") | Rated Capacity (Tons) | | | Master Link Diameter (") | Alloy Hook WLL Tons |
|---------------------|---------------|-----------------------|-----|-----|--------------------------|---------------------|
| | | Degrees | | | | |
| | | 60° | 45° | 30° | | |
| 6X19 OR 6X36 | 1/4 | 1.1 | .86 | .61 | 1/2 | 1 |
| | 5/16 | 1.5 | 1.2 | .86 | 1/2 | 1 |
| | 3/8 | 2 | 1.6 | 1.1 | 1/2 | 1-1/2 |
| | 7/16 | 2.7 | 2.2 | 1.5 | 3/4 | 2 |
| | 1/2 | 3.8 | 3.1 | 2.2 | 3/4 | 3 |
| | 9/16 | 4.7 | 3.8 | 2.7 | 7/8 | 5 |
| | 5/8 | 5.8 | 4.7 | 3.3 | 1 | 5 |
| | 3/4 | 8.2 | 6.7 | 4.7 | 1 | 5 |
| | 7/8 | 11 | 8.9 | 6.3 | 1-1/4 | 5 |
| 6X36 | 1 | 14 | 11 | 8 | 1-1/2 | 11 |
| | 1-1/8 | 17 | 14 | 10 | 1-1/2 | 11 |
| | 1-1/4 | 21 | 17 | 12 | 1-3/4 | 15 |
| | 1-3/8 | 24 | 20 | 14 | 1-3/4 | 22 |
| | 1-1/2 | 29 | 24 | 17 | 2 | 22 |
| | 1-3/4 | 38 | 31 | 22 | 2-1/4 | 30 |
| | 2 | 48 | 39 | 28 | 2-1/2 | 37 |



TYPE SS35 T-304: THREE LEG STAINLESS STEEL SLING

| | Rope Dia. (") | Rated Capacity (Tons) | | | Master Link Diameter (") | Alloy Hook WLL Tons |
|---------------------|---------------|-----------------------|-----|-----|--------------------------|---------------------|
| | | Degrees | | | | |
| | | 60° | 45° | 30° | | |
| 6X19 OR 6X36 | 1/4 | 1.6 | 1.3 | .91 | 3/4 | 1 |
| | 5/16 | 2.2 | 1.8 | 1.3 | 3/4 | 1 |
| | 3/8 | 3 | 2.4 | 1.7 | 7/8 | 1-1/2 |
| | 7/16 | 4 | 3.3 | 2.3 | 1 | 2 |
| | 1/2 | 5.6 | 4.6 | 3.2 | 1 | 3 |
| | 4/7 | 7.1 | 5.8 | 4.1 | 1 | 5 |
| | 5/8 | 8.6 | 7.1 | 5 | 1 | 5 |
| | 3/4 | 12 | 10 | 7.1 | 1-1/2 | 5 |
| | 7/8 | 16 | 13 | 9.5 | 1-3/4 | 5 |
| 6X36 | 1 | 21 | 17 | 12 | 1-3/4 | 11 |
| | 1-1/8 | 26 | 21 | 15 | 2 | 11 |
| | 1-1/4 | 31 | 25 | 18 | 2-1/4 | 15 |
| | 1-3/8 | 36 | 30 | 21 | 2-1/2 | 22 |
| | 1-1/2 | 43 | 35 | 25 | 2-1/2 | 22 |
| | 1-3/4 | 57 | 46 | 33 | 2-3/4 | 30 |



Rated Capacities based on design factor of 5.

Horizontal sling angles less than 30° shall not be used.