




HG-227



APPLICATION AND WARNING INFORMATION
SECTION 17

- End fittings are Quenched & Tempered or normalized, bodies heat-treated by normalizing.
- Hot-dip galvanized steel.
- Turnbuckles eyes are forged and elongated, by design, to maximize easy attachment in system and minimize stress in the eye. For turnbuckles size 1/4" through 2-1/2", a shackle one size smaller can be reeved through eye.
- Forged jaw ends are fitted with bolts and nuts for 1/4" through 5/8", and pins and cotters on 3/4" through 2-3/4" sizes.
- Modified UNJ thread on end fittings for improved fatigue properties.
- Body has UNC threads.
- TURNBUCKLES RECOMMENDED FOR STRAIGHT OR IN-LINE PULL ONLY.
- Lock nuts available for all sizes.
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load, and temperature requirements. Importantly, these turnbuckles meet other critical performance requirements including fatigue life, impact properties, and material traceability, not addressed by ASME B30.26.
- Meets the performance requirements of Federal Specifications FF-T-791b, Type 1 Form 1 - CLASS 8, and ASTM F-1145, except for those provisions required of the contractor. For additional information, see warnings and applications section.



HG-227 Jaw & Eye

Thread Dia. & Take Up (in)	Stock No.	Working Load Limit (lb)	Weight Each (lb)	Dimensions (in)												Replacement Pin Kit Stock No.
				00	B	E Closed	G	J Open	K Closed	M Open	N Closed	R	S	X Closed	BB	
* 5/16 x 4-1/2	1031895	800	.52	.25	.50	2.02	.87	13.50	9.00	14.30	9.80	.95	.44	2.20	4.58	1089654
* 3/8 x 6	1031911	1200	.80	.31	.53	2.11	.85	16.91	10.91	17.87	11.87	1.13	.53	2.48	6.10	1089672
1/2 x 6	1031939	2200	1.77	.37	.64	3.22	1.07	19.30	13.30	20.48	14.48	1.41	.71	3.56	6.03	1089690
1/2 x 9	1031957	2200	2.25	.37	.64	3.20	1.07	25.59	16.59	26.77	17.77	1.41	.71	3.54	9.36	1089690
1/2 x 12	1031975	2200	2.67	.37	.64	3.20	1.07	31.59	19.59	32.77	20.77	1.41	.71	3.54	12.36	1089690
5/8 x 6	1031993	3500	2.98	.50	.79	3.90	1.32	20.73	14.73	22.27	16.27	1.80	.88	4.35	6.03	1089716
5/8 x 9	1032019	3500	3.72	.50	.79	3.89	1.32	27.07	18.07	28.61	19.61	1.80	.88	4.34	9.39	1089716
5/8 x 12	1032037	3500	4.35	.50	.79	3.89	1.32	33.07	21.07	34.61	22.61	1.80	.88	4.34	12.39	1089716
3/4 x 6	1032055	5200	4.51	.63	.97	4.71	1.52	22.17	16.17	24.09	18.09	2.09	1.00	5.12	6.13	1097770
3/4 x 9	1032073	5200	5.56	.63	.97	4.68	1.52	28.57	19.57	30.49	21.49	2.09	1.00	5.09	9.59	1097770
3/4 x 12	1032091	5200	6.42	.63	.97	4.68	1.52	34.57	22.57	36.49	24.49	2.09	1.00	5.09	12.59	1097770
3/4 x 18	1032117	5200	8.14	.63	.97	4.71	1.52	46.57	28.57	48.49	30.49	2.09	1.00	5.12	18.53	1097770
7/8 x 12	1032135	7200	9.10	.75	1.16	5.50	1.77	35.68	23.68	37.91	25.91	2.38	1.25	5.79	12.16	1097789
7/8 x 18	1032153	7200	11.6	.75	1.16	5.50	1.77	48.15	30.15	50.38	32.38	2.38	1.25	5.79	18.63	1097789
1 x 6	1032171	10000	10.0	.88	1.34	6.09	2.05	25.03	19.03	27.59	21.59	3.00	1.43	6.50	6.18	1097761
1 x 12	1032199	10000	13.4	.88	1.34	6.09	2.05	37.03	25.03	39.59	27.59	3.00	1.43	6.50	12.18	1097761
1 x 18	1032215	10000	16.7	.88	1.34	6.09	2.05	49.03	31.03	51.59	33.59	3.00	1.43	6.50	18.18	1097761
1 x 24	1032233	10000	20.6	.88	1.34	6.06	2.05	61.63	37.63	64.19	40.19	3.00	1.43	6.47	24.84	1097761
1-1/4 x 12	1032251	15200	20.9	1.13	1.84	8.09	2.82	40.76	28.76	43.98	31.98	3.59	1.82	8.49	12.06	1097798
1-1/4 x 18	1032279	15200	24.8	1.13	1.84	8.09	2.82	52.76	34.76	55.98	37.98	3.59	1.82	8.49	18.06	1097798
1-1/4 x 24	1032297	15200	28.8	1.13	1.84	8.09	2.82	65.32	41.32	68.54	44.54	3.59	1.82	8.49	24.62	1097798
1-1/2 x 12	1032313	21400	30.6	1.38	2.06	8.93	2.81	42.50	30.50	46.21	34.21	4.09	2.12	9.46	12.32	1097805
1-1/2 x 18	1032331	21400	36.0	1.38	2.06	8.93	2.81	54.50	36.50	58.21	40.21	4.09	2.12	9.46	18.32	1097805
1-1/2 x 24	1032359	21400	41.5	1.38	2.06	8.93	2.81	67.12	43.12	70.83	46.83	4.09	2.12	9.46	24.94	1097805
1-3/4 x 18	1032395	28000	52.1	1.63	2.60	9.36	3.35	55.37	37.37	59.77	41.77	4.65	2.38	9.97	18.37	1097814
1-3/4 x 24	1032411	28000	59.7	1.63	2.60	9.36	3.35	67.37	43.37	71.77	47.77	4.65	2.38	9.97	24.37	1097814
2 x 24	1032439	37000	89.9	2.00	2.62	11.80	3.74	72.66	48.66	77.95	53.95	5.81	2.69	13.03	24.48	1097823
2-1/2 x 24	1032457	60000	158	2.25	3.06	13.26	4.44	76.08	52.08	82.68	58.68	6.49	3.12	13.76	24.60	1097832
2-3/4 x 24	1032475	75000	187	2.75	3.69	14.92	4.19	78.05	54.05	85.67	61.67	7.00	3.25	15.09	24.65	1087674

5:1 Design Factor. Proof Load is 2.5 times the Working Load Limit. *Mechanically galvanized